

Pointfix

All Weather Epoxy Jointing Mortar

Pointfix is a superior multi-purpose jointing and repair mortar that comes premixed with resins. This means there is no liquid to measure and mix and is easier to mix compared to sands or cement mortar. **Pointfix** comes as a two pack epoxy resin-based pointing mix that is specifically designed for pointing and infilling between many types of surfaces including concrete, natural stone, brick work and stone work.

Uses

We all know if it rains, or is forecast to rain, completing a project can become a major problem; especially when trying to point bricks and slabs. **Pointfix** eliminates this issue as it can be applied in the rain and can even cure under water.

Pointfix comes in a range of colours allowing a wide choice of design and gives consistent colour mixes. The 50/50 mixing ratio means you only use what is needed from the packs, cutting down on waste. **Pointfix** can be stored until required and leftover product can even be mixed with other colours.

How to Apply Pointfix

- Mix the **Pointfix** packs A and B together in a 50/50 ratio until uniform in colour;
- Add water and mix; if too much water is added, simply pour out the excess;
- Use this mixture to point slabs and bricks as normal brushing off any excess product;
- Leave to cure for **12 hours at 15-20 °C**; please note curing times are longer at lower temperatures and faster in warmer temperatures;
- Do not apply when temperatures may fall below 0 °C.
- For quicker applications, there is no need to add water, just apply with a broom;
- Where joints are deep, sand can be used to partially fill joints prior to pointing.

Technical Specifications

- Available in 24kg contractor packs or 12kg tub. As an example 12kg will point approximately 7.5m² using 600 x 600mm slabs with 10mm joint width, 24mm deep. Minimum depth for slabs is 12mm and for bricks is 3mm. There is no maximum depth or width;
- The quartz base is extremely hard with a hardness rating of 7 on the Mohs scale;
- The finished product is weather resistant, fade resistant and chemical resistant;
- No requirement for solvent or cement and does not stain;
- Colours available: Buff, Black, Mushroom and Grey.
- We try to keep our colours consistent but colours may vary between batches due to natural sand.
- Shelf life of 24 months and 12 months when opened providing bags are sealed.

Health and Safety

Please see GHS sticker on the side of the tub which include H302, H315, H317, H318 and H412 warnings.

Pave Fix Ltd, 10 Stag Business Park, Christchurch Road, Ringwood, Hampshire, BH24 3AS
Website: www.pavefix.co.uk email: info@pavefix.co.uk Telephone: 01425 478500

Whilst Pave Fix Limited endeavours to ensure that any advice recommendations specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.